

HazTech Systems, Inc. SAFETY DATA SHEET

Revision number: 2 Revision date: 06/29/2015

IDENTIFICATION 1.

Product name: **Product code:** Synonyms: CAS: **RTECS #** CI#: **Recommended use:** Uses advised against:

Company:

HazTech Systems, Inc. 3919 Bootjack Lane Mariposa, CA 95338 U.S.A. Telephone: 1-800-543-5487 / 1-209-966-8088 Fax: 1-209-966-8089 e-mail: sales@hazcat.com www.hazcat.com

HAZARD(S) IDENTIFICATION 2.

Classification of the substance or mixture **GHS-US classification**

Acute Tox. 4 (Oral) H302 Skin Corr. 1C H314 Eye Dam. 1 H318 STOT SE 3 H335 Aquatic Chronic 3 H412 Label elements

GHS-US labelling

Hazard pictograms (GHS-US)

Signal word (GHS-US) Hazard statements (GHS-US)

Precautionary statements (GHS-US)

Stannous chloride, Dihydrate **RE2322** tin chloride (SnCl2) dihydrate / tin dichloride dihydrate 10025-69-1 Not available Not available For laboratory and manufacturing use only. No information available

> Chemical Emergencies: HazTech Systems, Inc. (8:00am - 5:00pm) PST 1-800-543-5487 Transportation Emergencies: Chemtrec 24-Hour 1-800-424-9300 (U.S.A.) 1-703-527-3887 (International)



GHS05

- : Danger
- : H302 Harmful if swallowed
- H314 Causes severe skin burns and eve damage
 - H335 May cause respiratory irritation
- H412 Harmful to aquatic life with long lasting effects
- : P260 Do not breathe dust
- P264 Wash exposed skin thoroughly after handling
- P270 Do not eat, drink or smoke when using this product
- P271 Use only outdoors or in a well-ventilated area
- P273 Avoid release to the environment
- P280 Wear protective gloves, eye protection P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated
- clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing

- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes, Remove contact lenses, if present and easy to do. Continue rinsing
- P310 Immediately call a POISON CENTER or doctor/physician
- P363 Wash contaminated clothing before reuse

2. HAZARDS IDENTIFICATION				
	P405 - Store l	Store in a well-ventilated place ocked up se of contents/container to con		
Other hazards				
Other hazards not contributing to the classification	: None	e under normal conditions.		
Unknown acute toxicity (GHS-US)				
No data available				
3. COMPOSITION/INFORMATIC	N ON INGRI	EDIENTS		
Substance Substance type	: Mono	o-constituent		
Name		Product identifier	%	GHS-US classification
Stannous Chloride, Dihydrate (Main constituent)		(CAS No) 10025-69-1	100	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 3, H412
Full text of H-phrases: see section 16				
Mixture				
Not applicable 4. FIRST AID MEASURES				
Description of first aid measures First-aid measures general	. Ohar	ala tina a sital face ations a la sanca a		airway and respiration. Respiratory
	labou preve Keep Depe	ured breathing: half-seated. Vi ent asphyxia/aspiration pneum o watching the victim. Give psy ending on the victim's condition	ctim in shock: on his bac ionia. Prevent cooling by rchological aid. Keep the n: doctor/hospital.	rm resuscitation. Victim conscious with ck with legs slightly raised. Vomiting: y covering the victim (no warming up). a victim calm, avoid physical strain.
First-aid measures after inhalation				nsult a doctor/medical service.
First-aid measures after skin contact		h immediately with lots of wate its. Take victim to a doctor if in		o not apply (chemical) neutralizing
First-aid measures after eye contact		e immediately with plenty of w halmologist if irritation persists		alizing agents. Take victim to an
First-aid measures after ingestion	docto		nwell. Ingestion of large	ots of water to drink. Consult a quantities: immediately to hospital.
Most important symptoms and effects	both acute and	d delayed		
Symptoms/injuries after inhalation		ER INHALATION OF DUST: Cous membranes. Dry/sore thro		respiratory tract. Irritation of the nasal
Symptoms/injuries after skin contact	: Tingl	ling/irritation of the skin.		
Symptoms/injuries after eye contact	: Irritat	tion of the eye tissue.		
Symptoms/injuries after ingestion	: AFTE	ER ABSORPTION OF HIGH C	UANTITIES: Nausea. V	omiting. Diarrhea
Chronic symptoms	: ON C	CONTINUOUS/REPEATED EX	(POSURE/CONTACT: L	ung tissue affection/degeneration.
Indication of any immediate medical att	ention and spe	ecial treatment needed		
No additional information available				
5. FIREFIGHTING MEASURES				
Extinguishing media				
Suitable extinguishing media	: EXT	INGUISHING MEDIA FOR SU	RROUNDING FIRES: A	I extinguishing media allowed.
Unsuitable extinguishing media Special hazards arising from the subst	: No u	insuitable extinguishing media		
Fire hazard		SECT FIRE HAZARD. Non com	bustible.	
Explosion hazard	: D I RE		lo data available on dire	ct explosion hazard. INDIRECT
			anabio on munoor oxpre	

Reactivity	 Oxidizes slowly on exposure to air. Reacts violently with (strong) oxidizers. Decomposes on exposure to temperature rise: release of toxic and corrosive gases/vapours (hydrogen chloride) and formation of metallic fumes.
Advice for firefighters Precautionary measures fire	: Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: have neighbourhood close doors and windows.
Firefighting instructions	: Cool tanks/drums with water spray/remove them into safety. Dilute toxic gases with water spray.

: Heat/fire exposure: compressed air/oxygen apparatus. Heat/fire exposure: gas-tight suit.

Firefighting instructions Protection during firefighting

Stannous chionuc, Dinyurate	Revision Date 00/29/13
6. ACCIDENTAL RELEASE MEASURE	
Personal precautions, protective equipment	and emergency procedures
For non-emergency personnel	
Protective equipment	 Gloves, Face-shield. Protective clothing, Dust cloud production: compressed air/oxygen apparatus. Dust cloud production: dust-tight suit.
Emergency procedures	: Mark the danger area. Prevent dust cloud formation, e.g. by wetting. No naked flames. Wash contaminated clothes. In case of reactivity hazard: consider evacuation.
Measures in case of dust release	: In case of dust production: keep upwind. Dust production: have neighbourhood close doors and windows.
For emergency responders	
Protective equipment	: Equip cleanup crew with proper protection. Do not breathe dust.
Emergency procedures Environmental precautions	: Stop release. Ventilate area.
Prevent soil and water pollution. Prevent spread Methods and material for containment and c	•
For containment	Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the solid spill. Knock down/dilute dust cloud with water spray.
Methods for cleaning up	Stop dust cloud by covering with sand/earth. Scoop solid spill into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers, Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.
Reference to other sections	
No additional information available	
7. HANDLING AND STORAGE	
Precautions for safe handling	
Precautions for safe handling	: Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Avoid raising dust. Keep away from naked flames/heat. Observe strict hygiene. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
Conditions for safe storage, including any in	ompatibilities
ncompatible products	: Strong oxidizers. Strong acids. Strong bases. Halogens. alcohols.
⊣eat and ignition sources	: KEEP SUBSTANCE AWAY FROM: heat sources.
Prohibitions on mixed storage	: KEEP SUBSTANCE AWAY FROM: oxidizing agents. (strong) acids. (strong) bases. halogens. alcohols.
Storage area	: Store in a dry area. Meet the legal requirements.
Special rules on packaging	: SPECIAL REQUIREMENTS: hermetical. watertight. dry. clean. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
Packaging materials Specific end use(s)	: SUITABLE MATERIAL: glass. synthetic material.
No additional information available	

8. EXPOSURE CO

Stannous Chloride, Dihydrate (10025-69-1)			
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m³	
USA OSHA	OSHA PEL (TWA) (mg/m³)	2 mg/m³	
Exposure controls			

Exposure controls

Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation.
Materials for protective clothing	: GIVE GOOD RESISTANCE: butyl rubber. neoprene. PVC.
Hand protection	: Gloves.
Eye protection	: Face shield. In case of dust production: protective goggles.
Skin and body protection	 Protective clothing. In case of dust production: head/neck protection. In case of dust production: dustproof clothing.
Respiratory protection	: Dust production: dust mask with filter type P2. On heating: gas mask with filter type B.

9. PHYSICAL AND CHEMICAL PROPERTIES		
Information on basic physical and chemica	I properties	
Physical state	: Solid	
Appearance	: Crystalline solid.	
Molecular mass	: 225.63 g/mol	
Colour	: Colourless-white.	
Odour	: Irritating/pungent odour. Almost odourless.	
Odour threshold	: No data available	
рН	: No data available	
Relative evaporation rate (butylacetate=1)	: No data available	
Melting point	: 38 °C	
Freezing point	: No data available	
Boiling point	: Not applicable	
Flash point	: Not applicable	
Self ignition temperature	: No data available	
Decomposition temperature	: No data available	
Flammability (solid, gas)	: No data available	
Vapour pressure	: No data available	
Relative vapour density at 20 °C	: No data available	
Relative density	: 2.7	
Density	: 2710 kg/m³	
Solubility	: Soluble in water. Soluble in ethanol. Soluble in ether. Soluble in acetone. Soluble in ethylacetate. Soluble in sodium hydroxide solution. Soluble in hydrogenchloride. Water: 118 g/100ml	
Log Pow	: No data available	
Log Kow	: No data available	
Viscosity, kinematic	: No data available	
Viscosity, dynamic	: No data available	
Explosive properties	: No data available	
Oxidising properties	: No data available	
Explosive limits	: No data available	
Other information		
VOC content	: Not applicable	
Other properties	: Substance has acid reaction.	
10 STABILITY AND REACTIVITY		

10. STABILITY AND REACTIVITY

Reactivity

Oxidizes slowly on exposure to air. Reacts violently with (strong) oxidizers. Decomposes on exposure to temperature rise: release of toxic and corrosive gases/vapours (hydrogen chloride) and formation of metallic fumes.

Chemical stability Unstable on exposure to air. Possibility of hazardous reactions

Not established.

Conditions to avoid

Incompatible materials. Air contact.

Incompatible materials

Strong bases. Strong oxidizers. alcohols. Halogens. Hazardous decomposition products

Hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects Acute toxicity

: Harmful if swallowed.

Stannous Chloride, Dihydrate (\f)10025-69-1		
LD50 oral rat	700 mg/kg (RTECS)	
Skin corrosion/irritation	: Causes severe skin burns and eye damage.	
Serious eye damage/irritation	: Causes serious eye damage.	
Respiratory or skin sensitisation	: Not classified	
Germ cell mutagenicity	: Not classified	
Carcinogenicity	: Not classified	

Product Code(s) RE2322 Stannous chloride, Dihydrate

Stannous emonue, Dinyurate	Kevision Date 00/27/15
11. TOXICOLOGICAL INFORMATIO	ON
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposu	ure) : May cause respiratory irritation.
Specific target organ toxicity (repeated	: Not classified
exposure)	
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: AFTER INHALATION OF DUST: Coughing. Irritation of the respiratory tract. Irritation of the nas mucous membranes. Dry/sore throat. Respiratory difficulties.
Symptoms/injuries after skin contact	: Tingling/irritation of the skin.
Symptoms/injuries after eye contact	: Irritation of the eye tissue.
Symptoms/injuries after ingestion	: AFTER ABSORPTION OF HIGH QUANTITIES: Nausea. Vomiting. Diarrhoea.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Lung tissue affection/degeneration.
Likely routes of exposure	: Skin and eye contact;Inhalation
12. ECOLOGICAL INFORMATION	
Toxicity	
Ecology - air	: TA-Luft Klasse 5.2.2/III.
Ecology - water	: Mild water pollutant (surface water). Maximum concentration in drinking water: 250 mg/l (chloride) (Directive 98/83/EC). Harmful to aquatic organisms. pH shift.
Stannous Chloride, Dihydrate (10025-69)-1)
LC50 other aquatic organisms 1	37 mg/l (24 h; Daphnia magna; Anhydrous form)
EC50 other aquatic organisms 1	50.1 mg/l (96 h; Crangon sp.; Anhydrous form)
EC50 other aquatic organisms 2	71.8 mg/l (48 h; Crangon sp.; Anhydrous form)
Threshold limit other aquatic organisms 1	37 mg/l (24 h; Daphnia magna; Anhydrous form)
Persistence and degradability	
Stannous Chloride, Dihydrate (10025-69	-1)
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
Bioaccumulative potential	
No additional information available	
Mobility in soil	
No additional information available	
Other adverse effects	
No additional information available	
13. DISPOSAL CONSIDERATIONS	
Waste treatment methods	
Waste disposal recommendations	Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Recycle/reuse. Precipitate/make insoluble. Remove to an authorized dump (Class I).
Additional information	: LWCA (the Netherlands): KGA category 06. Hazardous waste according to Directive 2008/98/EC.
14. TRANSPORT INFORMATION	
In accordance with DOT	
	UN3260 Corrosive solid, acidic, inorganic, n.o.s. (Stannous Chloride, Dihydrate), 8, III
	3260 UN3260
	ON3260 Corrosive solid, acidic, inorganic, n.o.s.
	Stannous Chloride, Dihydrate 8 - Class 8 - Corrosive material 49 CFR 173.136
Classes	
Hazard labels (DOT) :	8 - Corrosive
DOT Symbols : 0	G - Identifies PSN requiring a technical name
	III - Minor Danger

Packing group (DOT)

: III - Minor Danger

Product Code(s) RE2322 Stannous chloride, Dihydrate

Stannous chloride, Dinydrate	Revision Date 06/29/15
14. TRANSPORT INFORMATION	
DOT Special Provisions (49 CFR 172.102)	 IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2). IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner. T1 - 1.5 178.274(d)(2) Normal 178.275(d)(2) TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 213
DOT Packaging Bulk (49 CFR 173.xxx)	: 240
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 25 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 100 kg
-	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Additional information	Na sumulamentary information sucilable
	No supplementary information available.
	Rail and road transport: not subject to ADR-RID.
Transport document description Transport by sea	
No additional information available Air transport	
No additional information available	
15. REGULATORY INFORMATION	
US Federal regulations	
Stannous Chloride, Dihydrate (10025-69-1)	
Not listed on the United States TSCA (Toxic Sub	ostances Control Act) inventory
International regulations CANADA	
Stannous Chloride, Dihydrate (10025-69-1)	
WHMIS Classification	Class E - Corrosive Material
EU-Regulations	
No additional information available	
Classification according to Regulation (EC) No	. 1272/2008 [CLP]
Acute Tox. 4 (Oral) H302 Eye Irrit. 2 H319 STOT SE 3 H335 Skin Irrit. 2 H315	
Aquatic Chronic 3 H412	
Full text of H-phrases: see section 16 Classification according to Directive 67/548/EE	FC or 1999/45/FC
Xn; R22 Xi; R36/37/38	
R52/53 Full text of R-phrases: see section 16	
National regulations	
No additional information available	
US State regulations	
No additional information available	

16. OTHER INFORMATION

Full

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1C	Skin corrosion/irritation, Category 1C
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard	: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
NFPA fire hazard	: 0 - Materials that will not burn.
NFPA reactivity	2 - Normally unstable and readily undergo violent decomposition but do not detonate. Also: may react violently with water or may form potentially explosive mixtures with water.
HMIS III Rating	
Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	: 0 Minimal Hazard
Physical	: 2 Moderate Hazard

: F

Revision Date: Prepared by:

Personal Protection

06/29/2015 HazTech Systems, Inc.

This information is based on HazTech Systems, Inc.'s, current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.